



# Insignia NS-PLTPSP13 Disassembly

This guide will show you how to disassemble the Insignia NS-PLTPSP13 speaker. This guide is to help you take apart your Insignia speaker for repair.

Written By: Madeleine



## INTRODUCTION

This guide will show you how to disassemble the Insignia NS-PLTPSP13 speaker. Using this guide, you should be able to access any components you need to repair or replace.

---



### TOOLS:

- [Metal Spudger](#) (1)
- [Tweezers](#) (1)
- [JIS Driver Set](#) (1)

Size J0

---

## Step 1 — Insignia NS-PLTPSP13 Disassembly



- Use the tweezers to lift the corner of the mesh until a gap is created.

## Step 2



- Once there is a gap big enough, insert the metal spudger, and remove the tweezers.



## Step 3



- Now take the size J0 JIS screwdriver to remove the seven 5 mm screws on the plastic casing of the speaker.
- Do not forget about the 5mm screw on the backside of the speaker, it may be covered by a white sticker, and it will prevent you from removing the plastic cover.

## Step 4



- Once all seven 5mm screws are taken off use the metal spudger again to pry off the plastic casing from the speaker.

## Step 5



- To further take apart the speaker, there are also two 5mm screws on the green circuit board which keep the speaker and circuit board attached. Unscrew these with the size J0 JIS screwdriver.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-06-24 01:20:12 AM.